

SUBCOMPACT GARDEN TRACTOR

SPECIFICATIONS

MODEL	LEGACY XL SUBCOMPACT GARDEN TRACTOR			
	27 2WD	27 4WD	27 4WD	27 4WD
ENGINE				
Make / Model	Kohler / Command™	Kohler / Command™	Kawasaki / LC	Briggs & Stratton / Diesel
Power Rating / Cylinders	27-gross hp†† / 2	27-gross hp†† / 2	27-gross hp††† / 2	27-gross hp† / 3
Muffler	High Performance			
Choke/Throttle	Separate Levers			
Fuel Tank Capacity	5.5 U.S. Gal.			
Battery (cca)	Front Mounted, 500cca			
TRANSMISSION				
Type	Tuff Torq® K92 Hydro (2WD)	Tuff Torq® K92 Hydro w/4WD		
Speed - Fwd (mph)	0 – 9			
Speed - Rev (mph)	0 – 5.5			
CHASSIS				
Frame	7-Gauge Steel			
Front Axle	Pivoting Cast Iron			
Rear Axle Diameter (inches)	1-5/32			
Turning Radius (inches)	28 (2WD)	55 (4WD engaged) / 35 (4WD disengaged)		
Front Turf Tread Tires	18 x 8.5 – 8 (4 ply)			
Rear Turf Tread Tires	26 x 12 – 12 (4 ply)			
Attachment Lift	Hydraulic, 4-way joystick			
Seat	18" Super High Back			
MOWER DECK				
Cutting Width (inches)	48, 54, 60 (Mower with deflector extended - 58, 64, 70)			
Height-of-Cut (inches)	1.0 – 5.0 Infinite			
# of Blades	3			
Rear Rollers	Full-Width, Follows Contours, Allows Striping			
Mower Removal	2 Quick Pins			
FEATURES				
Cruise Control	Standard			
Steering	Power Steering			
Tilt Steering Wheel	Standard			
Headlights	Halogen			
Hourmeter	Standard			
Fuel Level Indicator	Standard			
PTO Switch	Standard			
12 Volt DC Outlet	Standard			
Cup Holder	Standard			
Tool Box	Standard			
Hand Grip Fender Rails	Standard			
Parking Brake	Standard			
DIMENSIONS				
L x W x H (inches)	81 x 45* x 51			
Wheel Base (inches)	59			
Weight (lbs) w/o Mower	830	980	1030	1131

†All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

††Kohler Engine Power Rating: Kilowatt (kW) and horsepower (HP) specifications for Kohler general purpose engines are calculated pursuant to the Society of Automotive Engineers (SAE) J1940 for horsepower ratings - calculated with the air cleaner and muffler removed, per the SAE standard. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude).

†††All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

*Width equals tractor only.

YARD & GARDEN TRACTOR

SPECIFICATIONS

MODEL	PRESTIGE GARDEN TRACTOR				CONQUEST YARD TRACTOR		
	27 2WD	27 4WD	30 2WD	30 4WD	23/46	24/52	24/52 PS
ENGINE							
Make / Model	Kohler / Command™		Briggs & Stratton Professional Series™ with Electronic Fuel Management		Kohler / Courage™	Briggs & Stratton Professional Series™ with Electronic Fuel Management	
Power Rating / Cylinders	27-gross hp†† / 2		30-gross hp† / 2		23-gross hp†† / 2	24-gross hp† / 2	
Muffler	Quiet, Compact, Low Back Pressure				Quiet, Compact, Low Back Pressure		
Choke/Throttle	Separate Levers				Separate Levers		
Fuel Tank Capacity	4.0 U.S. Gal.				4.0 U.S. Gal.		
Battery (cca)	Front Mounted, 500cca				Front Mounted, 340cca		
TRANSMISSION							
Type	Tuff Torq® K71 Hydro (2WD)	Kanzaki HFWD (ION) / Tuff Torq K664	Tuff Torq® K71 Hydro (2WD)	Kanzaki HFWD (ION) / Tuff Torq K664	Tuff Torq® K66 Hydro		
Speed - Fwd (mph)	0 – 7.2	0 – 6.1	0 – 7.2	0 – 6.1	0 – 6.1		
Speed - Rev (mph)	0 – 4.5	0 – 3.0	0 – 4.5	0 – 3.0	0 – 3.0		
CHASSIS							
Frame	10-Gauge Steel (Mower deck steel is also 10-gauge thick)				10-Gauge Steel		
Front Axle	Pivoting Cast Iron				Pivoting Cast Iron with 1-inch Diameter Spindles		
Rear Axle Diameter (inches)	1.0				1.0		
Turning Radius (inches)	18 (2WD)	30 (4WD)	18 (2WD)	30 (4WD)	18		
Front Turf Tread Tires	16 x 6.5 – 8				16 x 6.5 – 8		
Rear Turf Tread Tires	24 X 12 - 12	23 x 10.5 – 12	24 X 12 - 12	23 x 10.5 – 12	23 x 10.5 – 12		
Attachment Lift	Hydraulic				Manual with Spring Assist		
Seat	18" Adjustable				18" Adjustable		
MOWER DECK							
Cutting Width (inches)	46, 54				46	52	
Height-of-Cut (inches)	1.0 – 4.0 Infinite				1.0 – 4.0 Infinite		
# of Blades	3				3		
Rear Rollers	Full-Width, Follows Contours, Allows Striping				Full-Width, Follows Contours, Allows Striping		
Mower Removal	Quick Hitch™ Removal System				Quick Hitch™ Removal System		
FEATURES							
Cruise Control	Standard				Standard		
Steering	Power Steering				Low-Effort	Low-Effort	Power Steering
Tilt Steering Wheel	Standard				N/A		
Headlights	4-Bulb				4-Bulb		
Hourmeter	Standard				Standard		
Fuel Level Indicator	Digital Gauge				Digital Gauge		
PTO Switch	Standard				Standard		
12 Volt DC Outlet	Standard				Standard		
Cup Holder	Standard				Standard		
Tool Box	Standard				Standard		
Hand Grip Fender Rails	Standard				Standard		
Parking Brake	Standard				Standard		
DIMENSIONS							
L x W x H (inches)	75 x 56* (46-in. deck) 64* (54-in. deck) x 50				75 x 56* x 47	75 x 62* x 47	75 x 62* x 47
Wheel Base (inches)	53				53	53	53
Weight (lbs) with Mower	740	815	746	815	670	680	700

†All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

††Kohler Engine Power Rating: Kilowatt (kW) and horsepower (HP) specifications for Kohler general purpose engines are calculated pursuant to the Society of Automotive Engineers (SAE) J1940 for horsepower ratings - calculated with the air cleaner and muffler removed, per the SAE standard. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude).

*Width equals tractor only.

HEAVY-DUTY LAWN TRACTOR

SPECIFICATIONS

MODEL	BROADMOOR		
	22/44	20/46	20/52
ENGINE			
Make / Model	Briggs & Stratton / Professional Series™ EFM		Briggs & Stratton / Vanguard™
Power Rating / Cylinders	22-gross hp† / 2		20-gross hp† / 2
Muffler	Quiet, Compact, Low Back Pressure		
Choke/Throttle	Separate Levers		
Fuel Tank Capacity	4.0 U.S. Gal.		
Battery (cca)	Front Mounted, 230cca		
TRANSMISSION			
Type	Tuff Torq® K57 Hydro		
Speed - Fwd (mph)	0 – 5.8		
Speed - Rev (mph)	0 – 3.5		
CHASSIS			
Frame	10-Gauge Steel		
Front Axle	Pivoting Cast Iron		
Rear Axle Diameter (inches)	.75		
Turning Radius (inches)	18		
Front Turf Tread Tires	15 x 6.0 – 6		
Rear Turf Tread Tires	22 x 10.0 – 10		
Attachment Lift	Manual		
Seat	15" Adjustable		
MOWER DECK			
Cutting Width (inches)	44	46	52
Height-of-Cut (inches)	1.0 – 3.75 Infinite, Electric	1.0 – 4.0 Infinite, Electric	1.0 – 4.0 Infinite, Electric
# of Blades	3	3	3
Rear Rollers	Full-Width, Follows Contours, Allows Striping		
Mower Removal	Quick Hitch™ Removal System		
FEATURES			
Cruise Control	Standard		
Steering	Low-Effort		
Headlights	4-Bulb		
Hourmeter	Standard		
Fuel Level Indicator	Gauge		
PTO Switch	Standard		
12 Volt DC Outlet	Standard		
Cup Holder	Standard		
Tool Box	Standard		
Hand Grip Fender Rails	Standard		
Parking Brake	Standard		
DIMENSIONS			
L x W* x H (inches)	71 x 50* x 43	71 x 56* x 43	71 x 62* x 43
Wheel Base (inches)	53	53	53
Weight (lbs) with Mower	600	607	610

*Width equals mower with deflector extended.

We reserve the right to change specifications, features and pricing without notice. Product may vary from images shown.

MODEL	REGENT EX			REGENT	CORONET
	21/38	23/46	26/52	21/42	13.5/30
ENGINE					
Make / Model	Briggs & Stratton / Professional Series™				Briggs & Stratton / Intek™
Power Rating / Cylinders	21-gross hp† / 1	23-gross hp† / 2	26-gross hp† / 2	21-gross hp† / 2	13.5-gross hp† / 1
Muffler	Quiet, Enclosed / 5" Deluxe				Quiet, Compact
Choke/Throttle	Separate Levers			Single Lever	Single Lever
Fuel Tank Capacity	3.5 U.S. Gal. with Large Filler Neck				2.0 U.S. Gal.
Battery (cca)	Front Mounted, 230cca				230cca
TRANSMISSION					
Type	Tuff Torq® K46 Hydro		Tuff Torq® K46 Hydro	HydroGear T2HP	Hydro-Gear® Hand Control
Speed - Fwd (mph)	0 – 5.5			0 – 5.6	0 – 5.0
Speed - Rev (mph)	0 – 3.0			0 – 3.5	0 – 2.3
CHASSIS					
Frame	12-Gauge Steel				14-Gauge Steel, Deep Drawn Steel
Front Axle	Pivoting Cast Iron				Formed Steel
Rear Axle Diameter (inches)	.75				.75
Turning Radius (inches)	14				12
Front Turf Tread Tires	15 x 6.0 – 6				13 x 5.0 – 6
Rear Turf Tread Tires	20 x 8.0 – 8	22 x 10.0 – 8	20 x 10.0 – 8		16 x 6.5 – 8
Attachment Lift	Manual				Manual
Seat	15" with Coil Springs			Mid Back	13"
MOWER DECK					
Cutting Width (inches)	38	46	52	42	30
Height-of-Cut (inches)	1.0 – 4.0 Infinite		1.5 – 4.0 Infinite	1.0 – 4.0	1.0 – 3.75 Infinite
# of Blades	2	3	3	2	1
Rear Rollers	Full-Width, Follows Contours, Allows Striping			Fixed Roller	Gauge Wheels
Mower Removal	Quick Hitch™ Removal System			Frame Mtg.	Quick Hitch™ Removal System
FEATURES					
Cruise Control	Standard				N/A
Steering	Manual				Manual
Headlights	Standard				N/A
Hourmeter	Optional	Standard		N/A	N/A
Fuel Level Indicator	Fuel Level Window				Translucent Fuel Tank
PTO Switch	Standard				Standard
12 Volt DC Outlet	N/A				N/A
Cup Holder	Standard				N/A
Tool Box	Standard				N/A
Hand Grip Fender Rails	Standard				N/A
Parking Brake	Standard				Standard
DIMENSIONS					
L x W* x H (inches)	71 x 50* x 45	71 x 56* x 45	71 x 62* x 45	71 x 52* x 42	61 x 36* x 41
Wheel Base (inches)	50	50	50	50	43
Weight (lbs) with Mower	502	552	585	532	415

†All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

‡ All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

*Width equals riding mower with deflector extended.

We reserve the right to change specifications, features and pricing without notice. Product may vary from images shown.

MODEL	COBALT			
	32/61	30/61	30/61	26/61
ENGINE				
Make / Model	Briggs & Stratton / Vanguard™ Big Block™		Briggs & Stratton / Commercial Turf	Kawasaki V-Twin
Power Rating / Cylinders	32-gross hp† / 2	30-gross hp† / 2		26-gross hp†† / 2
Muffler	Extra Quiet			
Oil Filter	Spin-On			
Choke/Throttle	Separate Levers			
Fuel Tank	11.0 U.S. Gal.			
Battery	340cca			
TRANSMISSION				
Make	Hydro-Gear®			
Type	BP12A Pump / HGM – 12 Motor			
Speed – Fwd / Rev	0 – 10.0 / 0 – 6.0			
Brakes	Band			
CHASSIS				
Frame	1.5" x 2" Welded Steel Tube			
Front Axle	Patented Suspension System			
Suspension	4-Wheel			
Front Tires (inches)	13, Smooth Tread			
Rear Tires (inches)	22 x 11, Turf Tread			
Adjustable Seat	18" with Arm rests			
MOWER DECK				
Cutting Width (inches)	61			
Height-of-Cut Adjustment	14 positions			
Height-of-Cut Range	1.75" – 5.0"			
# of Blades	3			
Mower Lift	Foot Assist			
Discharge Deflector	Flexible, Pivoting			
Full Width Rear Rollers	Standard			
Anti-Scalp Wheels	Standard			
FEATURES				
Steering	Twin-Lever, Adjustable Fore/Aft			
Parking Brake	Lever			
Hour meter	Standard			
Headlights	Standard			
PTO Switch	Commercial Heavy-Duty, Electric			
12V DC Outlet	N/A			
Storage Area/Cup holder	Standard			
Engine Cover	N/A			
ROPS	Folding			
DIMENSIONS				
L x W* x H (inches)	83 x 74 x 70			
Wheel Base (inches)	55			
Weight (lbs)	1210			
WARRANTY				
Residential Use	2 Years Ltd. (Engine & Machine)			
Commercial Use	2 Years (Engine) 1 Year (Machine)			

ZERO-TURN RIDING MOWER

SPECIFICATIONS

MODEL	CITATION			ZT4000	ZT3500
	28/61	26/52	22/52	27/48	27/48
ENGINE					
Make / Model	Briggs & Stratton / Commercial Turf		Kawasaki V-Twin	Briggs & Stratton / Professional Series™	Briggs & Stratton / Professional Series™
Power Rating / Cylinders	28-gross hp† / 2	26-gross hp† / 2	22-gross hp†† / 2	27-gross hp† / 2	27-gross hp† / 2
Muffler	Extra Quiet		Low Noise, Extra Large	Low Noise, Extra Large	
Oil Filter	Spin-On		Spin-On	Spin-On	
Choke/Throttle	Separate Levers		Separate Levers	Separate Levers	
Fuel Tank	5.5 U.S. Gal.		5.5 U.S. Gal.	5.5 U.S. Gal.	
Battery	340cca		340cca	340cca	
TRANSMISSION					
Make	Hydro-Gear®		Hydro-Gear®	Hydro-Gear®	
Type	BDP-10A Pump / HGM – 12 Motor		10A Pump / 12 Motor	Twin Transaxle	
Speed – Fwd / Rev	0 – 9.0 / 0 – 5.0		0 – 8.0 / 0 – 5.0	0 – 8.0 / 0 – 4.0	
Brakes	Band		Band	Internal	
CHASSIS					
Frame	1.5" x 2" Welded Steel Tube		1.5" x 2" Welded Steel Tube	1.5" x 2" Welded Steel Tube	
Front Axle	Pivoting with Shocks		Pivoting with Shocks	Fabricated	
Suspension	Front & Rear		Front & Rear	-	
Front Tires (inches)	13, Smooth Tread		11 x 4 – 5	11 x 4 – 5	
Rear Tires (inches)	22 x 11, Turf Tread		20 x 8, Turf Tread	20 x 10, Turf Tread	
Adjustable Seat	18" with Arm rests		18" High-Back	18" High-Back	
MOWER DECK					
Cutting Width (inches)	61	52	52	48	48
Height-of-Cut Adjustment	14 positions		12 positions	12 positions	
Height-of-Cut Range	1.75" – 5.0"		1.5" – 4.5"	1.5" – 4.5"	
# of Blades	3		3	3	
Mower Lift	Foot Assist		Foot Assist	Foot Assist	
Discharge Deflector	Flexible, Pivoting		Flexible, Pivoting	Flexible, Pivoting	
Full Width Rear Rollers	Standard		Standard	-	
Anti-Scalp Wheels	Standard		Standard	Standard	
FEATURES					
Steering	Twin-Lever, Adjustable Fore/Aft		Twin-Lever, Adjustable Fore/Aft	Twin-Lever, Adjustable Fore/Aft	
Parking Brake	Lever		Lever	Lever	
Hour meter	Standard		Standard	Standard	
Headlights	Standard		Optional	Optional	
PTO Switch	Commercial Heavy-Duty, Electric		Electric	Electric	
12V DC Outlet	N/A		N/A	N/A	
Storage Area/Cup holder	N/A		Standard	Standard	
Engine Cover	N/A		N/A	N/A	
ROPS	Folding		Standard	N/A	
DIMENSIONS					
L x W* x H (inches)	79.5 x 74 x 70	79.5 x 64 x 70	79.5 x 64 x 70	78 x 60 x 42	69 x 64 x 40
Wheel Base (inches)	48	48	48	49	45
Weight (lbs)	1097	1063	1063	1012	724
WARRANTY					
Residential Use	2 Years Ltd. (Engine & Machine)		2 Years Ltd. (Engine & Machine)	2 Years Ltd. (Engine & Machine)	
Commercial Use	2 Years (Engine) 1 Year (Machine)		1 Year (Engine) 90 Days (Machine)	1 Year (Engine) 90 Days (Machine)	

†All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

†† All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

*Width equals riding mower with deflector extended.

We reserve the right to change specifications, features and pricing without notice. Product may vary from images shown.

ZERO-TURN RIDING MOWERS

SPECIFICATIONS

MODEL	ZT2500		ZT2000	ZT1500	
	27/52	24/46	26/52	22/46	21/42
ENGINE					
Make / Model	Briggs & Stratton / Professional Series™ V-Twin/EFM		Briggs & Stratton / Professional Series™ V-Twin	Briggs & Stratton / Professional Series™	
Power Rating / Cylinders	27-gross hp† / 2	24-gross hp† / 2	26-gross hp† / 2	22-gross hp† / 2	21-gross hp† / 1
Muffler	Low Noise, Extra Large		Clam Shell, Under Frame		
Oil Filter	Spin-On		Spin-On		
Choke/Throttle	Separate Levers		Choke-a-Matic		
Fuel Tank	5.0 U.S. Gal.		3.0 U.S. Gal.		
Battery	340cca		12V / 230cca		12V / 190cca
TRANSMISSION					
Make	Hydro-Gear®		Hydro-Gear® EZT®		
Type	10A Pump / 12 Motor		Sealed Hydro Transaxle		
Speed – Fwd / Rev	0 – 7.0 / 0 – 5.0		0 – 6.0 / 0 – 3.0		
Brakes	Drum		Internal		
CHASSIS					
Frame	1.5" x 2" Welded Steel Tube		12-Gauge One-Piece Formed Steel		
Front Axle	Pivoting with Shocks		Cast-Iron		
Suspension	Front & Rear		-		
Front Tires (inches)	11 x 4 – 5		11.00 x 4.00 2-ply smooth tread		
Rear Tires (inches)	20 x 8 – 10 (4 ply)		20 x 10, Turf Tread	18.00 x 9.50	18.00 x 8.50 Turf Tread
Adjustable Seat	18", Adjustable Fore/Aft		5-position, no tools w/ arm rests		5-position, no tools Wing Knobs
MOWER DECK					
Cutting Width (inches)	52	46	52	46	42
Height-of-Cut Adjustment	7 Position		Infinite		
Height-of-Cut Range	1.5" – 4.5"		1.5" – 3.75"		
# of Blades	3	3	3	3	2
Mower Lift	Manual		Electric		
Discharge Deflector	Molded, Pivoting		Molded, Pivoting		
Full Width Rear Rollers	Standard		-		
Anti-Scalp Wheels	Standard		Standard		
FEATURES					
Steering	Twin-Lever, Adjustable Fore/Aft		Twin-Lever		
Parking Brake	Lever		Separate Lever		
Hour meter	Standard		Standard		
Headlights	Optional		N/A		
PTO Switch	Electric		Electric Blade Engage Clutch		
12V DC Outlet	N/A		N/A		
Storage Area/Cup holder	Standard		Standard		
Engine Cover	N/A		N/A		
ROPS	N/A		N/A		
DIMENSIONS					
L x W* x H (inches)	78 x 62 x 42	75 x 62 x 39	75 x 56 x 39	75 x 62 x 39	75 x 56 x 39 75 x 52 x 39
Wheel Base (inches)	49	48	48	48	48
Weight (lbs)	723	625	604	554	545 530
WARRANTY					
Residential Use	2 Years Ltd. (Engine & Machine)		2 Years Ltd. (Engine & Machine)		2 Years Ltd. (Engine & Machine)
Commercial Use	1 Year (Engine) 90 Days (Machine)		1 Year (Engine) 90 Days (Machine)		1 Year (Engine) 90 Days (Machine)

Intek™, Professional Series™, Vanguard™, Big Block™, 1450 Series™, 900 Series™, 825 Series™, 800 Series™, 700 Series™, 650 Series™, 550 Series™ are trademarks used by Briggs & Stratton Corporation. Courage™ and Command™ are trademarks used by the Kohler Company. Marbain® is a registered trademark of The Fisher-Barton Group. Tuff Torq® is a registered trademark of Tuff Torq Corporation. Hydro-Gear® EZT® is a registered trademark of Hydro-Gear Inc.